| Ref # | Hits | Search Query | DBs | Default Operator | Plurals | Time Stamp |
|----------|-------------------|---|---|---------------------|---------|------------------|
| L1 | 2 | (("6457627") or ("5662261")).PN. | USPAT | OR | OFF | 2005/06/15 09:33 |
| L3 | 859 | wire adj bond\$4 and wire near (diameter) | USPAT | OR- | OFF | 2005/06/15 09:34 |
| L4 | 10 | 3 and (wire near (diameter) near (micron or micrometer or ".mu.m")) | USPAT | OR | OFF | 2005/06/15 09:34 |
| L5 | 44 052 | (capillary or bond\$4 adj tool) and (angl\$4 or inclin\$6) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2005/06/15 09:38 |
| L6 | 3841 | 5 and (angl\$4 or inclin\$6) near (face or surface) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2005/06/15 09:38 |
| L10 | 640 | 6 and (angl\$4 or inclin\$6) near (degree or ".degree." or theta or alpha or omega) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2005/06/15 09:42 |
| L11 | 34 | 10 and wire near bond\$4 | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2005/06/15 09:42 |
| L12 | 27 | 11 and (force or load or pressure) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2005/06/15 09:43 |
| L13 | 31 | 11 and (semiconductor or chip or die) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2005/06/15 09:43 |
| L14 | 26 | 13 and (force or load or pressure) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2005/06/15 09:55 |

| L15 | 1 | 11 and height near face | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR . | ON | 2005/06/15 09:48 |
|-----|----|-------------------------|---|------|----|------------------|
| L16 | 25 | 14 not 15 | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | ON | 2005/06/15 10:00 |

Searching PAJ



| Search Results: 21 | Index Indication | Clear | | | | | |
|---|------------------------------|------------------------------------|--|--|--|--|--|
| Text Search If you want to conduct a Number S | earch, please click on the t | outton to the right. Number Search | | | | | |
| Applicant, Title of invention, Abstract — e.g. computer semiconductor | | | | | | | |
| If you use the AND/OR operation, please leave a SPACE between keywords. One letter word or Stopwords are not searchable. | | | | | | | |
| capillary wire face | | AND ▼ | | | | | |
| | AND | | | | | | |
| angle incline | • | OR ▼ | | | | | |
| | AND | | | | | | |
| bond attach | | OR 🔻 | | | | | |
| | AND . | | | | | | |
| Date of publication of application — e.g.19980401 - 19980405 | | | | | | | |
| | - | | | | | | |
| | AND | | | | | | |
| IPC e.g. D01B7/04 A01C11/02 | | | | | | | |
| If you use the OR operation, please leave a SPACE between keywords. | | | | | | | |
| • | | | | | | | |
| | | | | | | | |
| . Search Stored data | | | | | | | |

Copyright (C); 1998,2003 Japan Patent Office